

Backlit Banner Textil

PRODUCT CODE: SDB190

FEATURES / APPLICATIONS:

- 100% woven polyester fabric with white surface
- For SEG Light Box and frame and Pop-up materials
- Compatible with Dye-sub direct, Dye-sub transfer, also workable with Latex inks

MATERIAL DETAILS

| PROPERTIES | TEST METHOD | METRIC | IMPERIAL |
|--------------------------------|--------------------------------|--|---------------|
| Total Weight | DIN EN ISO 2286-2,ASTM D 751 | 190 g/sq.m | 5.58 oz/sq.yd |
| Base Fabric | DIN 60001,ASTM D7641 | 100%Polyester | 100%Polyester |
| Yarn Dtex | DIN EN ISO 2060,ASTM D 1907 | 83x165 dtex | 75x150 denier |
| Weave Method | N/A | Woven | |
| Shrinkage | 195°C , 42SEC | Warp≤2%,Weft≤3% | |
| Light Transmittance | ANSI PH2.19, ISO 5/2 | (48±6)% | |
| Flame Resistance | DIN 4102-1-B1 , NFPA 701 Test1 | DIN 4102-1-B1 , NFPA 701 Test1 | |
| Recommend Fixation Temperature | N/A | 190°C-210°C , 1-2min | |
| Transfer Temperature | N/A | 190°C-210°C , 1-2min | |
| Yellowing temperature | 30s | ≥210°C | |
| Width | DIN EN ISO 3759,ASTM D751-2006 | Max 320cm | 126" |
| Standard Length | DIN EN ISO 3759,ASTM D751-2006 | 50m | 55yd |
| Compatiable Inks | N/A | Dye-sub Transfer, Dye-sub Direct,UV,Latex | |
| Application | N/A | Light Box&Bakclit,Exhibition&Events,Frame Display, Indoor Deco | |

INK PRINTABILITY

| Solvent | Eco Solvent | UV | Latex |
|-----------------|--------------------------|--------------------------|--------------------------|
| | | <input type="checkbox"/> | <input type="checkbox"/> |
| Screen Printing | Dye Transfer | Dye Direct | |
| | <input type="checkbox"/> | <input type="checkbox"/> | |

NOTE: All above information shall only used as a guide; buyers shall independently test and determine the products suitability. The mentioned data are average of test result and should not be used for the purpose of lawsuit or warranty